



# Virtuozzo 7 Installation Using PXE

July 25, 2016

Parallels IP Holdings GmbH  
Vordergasse 59  
8200 Schaffhausen  
Switzerland  
Tel: + 41 52 632 0411  
Fax: + 41 52 672 2010  
<http://www.virtuozzo.com>

Copyright © 1999-2016 Parallels IP Holdings GmbH and its affiliates. All rights reserved.

This product is protected by United States and international copyright laws. The product's underlying technology, patents, and trademarks are listed at <http://www.virtuozzo.com/legal/>.

Microsoft, Windows, Windows Server, Windows NT, Windows Vista, and MS-DOS are registered trademarks of Microsoft Corporation.

Apple, Mac, the Mac logo, Mac OS, iPad, iPhone, iPod touch, FaceTime HD camera and iSight are trademarks of Apple Inc., registered in the US and other countries.

Linux is a registered trademark of Linus Torvalds.

All other marks and names mentioned herein may be trademarks of their respective owners.

# Table of Contents

1. Introduction .....	4
2. Preparing for PXE Installation .....	5
2.1. Choosing Servers .....	5
2.2. Installing Software on the PXE Server .....	5
2.3. Configuring the TFTP Server .....	6
2.4. Setting Up a DHCP Server .....	7
2.5. Setting Up an HTTP Server .....	7
2.6. Configuring the Virtuozzo Server .....	8
3. Installing Virtuozzo 7 .....	9
4. Creating a Kickstart File .....	10
4.1. Standard Kickstart Options .....	10
4.2. Virtuozzo Kickstart Options .....	11
4.3. Kickstart File Example .....	16
4.3.1. Kickstart file example for installing on EFI-based systems .....	17
4.4. Copying the Kickstart File .....	17
4.5. Starting Installation .....	18

# Chapter 1. Introduction

This guide provides information on installing Virtuozzo over network using preboot execution environment (PXE) server.

You can install Virtuozzo in a PXE environment using one of the following ways:

- **Manual installation.** When performing this kind of installation, you are asked questions by the Virtuozzo installer and define the necessary installation and configuration settings. Manual installation is recommended if you plan to install the product on a small number of physical servers.
- **Unattended installation.** In this kind of installation, the Virtuozzo installer uses a kickstart file to determine the necessary installation and configuration settings. Unattended installation assumes that no interaction is required on your part and is recommended if you plan to install the product on a multitude of physical servers.

To install Virtuozzo 7 over a network, you need to complete the following steps:

1. Prepare for installation from a PXE server.
2. Create a kickstart file. This step is only required if you plan to automate the procedure of deploying Virtuozzo on your servers.
3. Install Virtuozzo.

All these steps are explained in the following chapters in detail.

# Chapter 2. Preparing for PXE Installation

The process of preparing for installation over network with a PXE server includes the following steps:

1. Choosing servers for the PXE installation.
2. Installing the necessary software on the PXE server.
3. Configuring the TFTP server.
4. Setting up a DHCP server.
5. Setting up an HTTP server.
6. Configuring the Virtuoizzo server.

All these steps are described below in detail.

## 2.1. Choosing Servers

First, you should decide on the servers to participate in the PXE installation. You need these servers:

- **PXE server.** This is a server allowing your servers to boot and install Virtuoizzo over the network. Any server capable of running a Linux operating system and having a network interface card (NIC) can play the role of a PXE server.
- **DHCP server.** This is a standard DHCP server serving computers on your network with the necessary TCP/IP settings. You can use an existing DHCP server, if you have one, or set up a DHCP server from scratch. In the latter case, you can install it on the PXE server or use a dedicated server.
- **Virtuoizzo server.** This is a server running Virtuoizzo. The server must meet the requirements described in the **Preparing for Installation** chapter of the *Virtuoizzo 7 Installation Guide*. In addition to the requirements listed in this chapter, the server must have a NIC with PXE support to be able to boot from the PXE server.
- **HTTP or FTP server.** This is a server storing the Virtuoizzo installation files. You can use an existing HTTP server, if you have one, or set up an HTTP server from scratch. In the latter case, you can install it on the PXE server or use a dedicated server.

This guide assumes that you will store the installation files on an HTTP server and use HTTP as the installation protocol.

## 2.2. Installing Software on the PXE Server

Next, you are supposed to install the necessary software on the PXE server. First of all, you need to install a Linux operating system on the server. There are no specific requirements for which operating system to use, so you can choose any (e.g., CentOS 6 or Fedora 17).

Once your system is up and running, install the following packages:

- `tftp-server`
- `httpd` (Install this package only if you plan to deploy the PXE and HTTP servers on the same physical server.)

- `syslinux`
- `dhcp` (Install this package only if you plan to deploy the PXE and DHCP servers on the same physical server.)

Assuming that your PXE server is running an RHEL-like operating system, you can use the `yum` utility to install the packages:

```
# yum install tftp-server dhcp httpd syslinux
```

## 2.3. Configuring the TFTP Server

In the next step, you need to configure the TFTP server that you installed in the previous step. This section describes the process of configuring the TFTP server for BIOS-based systems. For information on how to configure the TFTP server for installing Virtuozzo on EFI-based systems, see **Configuring for EFI** in the *Red Hat Enterprise Linux Installation Guide* at [https://access.redhat.com/knowledge/docs/en-US/Red\\_Hat\\_Enterprise\\_Linux/6/html/Installation\\_Guide/s1-netboot-pxe-config-efi.html](https://access.redhat.com/knowledge/docs/en-US/Red_Hat_Enterprise_Linux/6/html/Installation_Guide/s1-netboot-pxe-config-efi.html).

To configure the TFTP server:

1. On the PXE server, open the `/etc/xinetd.d/tftp` file, and edit it as follows:

```
service tftp
{
  disable          = no
  socket_type      = dgram
  protocol         = udp
  wait            = yes
  user             = root
  server           = /usr/sbin/in.tftpd
  server_args      = -v -s /tftpboot
  per_source       = 11
  cps              = 100 2
  flags            = IPv4
}
```

Once you are done, save the file.

2. Copy the following files to the `/tftpboot` directory (if this directory does not exist, create it under the root `(/)` directory):
  - `mlinuz`
  - `initrd.img`
  - `menu.c32`
  - `pxelinux.0`

These files are necessary to start the installation of Virtuozzo. You can find the first two files in the `/isolinux` directory of the Virtuozzo distribution. The `menu.c32` and `pxelinux.0` files are located in the `syslinux` installation directory on the PXE server (usually, this is the `/usr/share/syslinux` or `/usr/lib/syslinux` directory).

3. Create the `/tftpboot/pxelinux.cfg` directory, and inside this directory, make the `default` file.
4. Open the `default` file for editing, and add the following strings to it:

```
default menu.c32
prompt 0
timeout 100
ontimeout VZ
menu title Virtuoizzo Boot Menu
label VZ
    menu label Install Virtuoizzo
    kernel vmlinuz
    append initrd=initrd.img ksdevice=eth0
```

For detailed information on the parameters you can specify in the `/tftpboot/pxelinux.cfg/default` file and their configuration, see the documentation for `syslinux` and its man pages.

5. Restart the `xinetd` service:

```
# /etc/init.d/xinetd restart
```

6. If necessary, configure your firewall on the PXE server to allow access to the TFTP server.

**Note:** When running the TFTP server, you might get the "**Permission denied**" error. In this case, you may try to fix the problem by running the following command on the server: `# restorecon -Rv /tftpboot/`.

## 2.4. Setting Up a DHCP Server

Now you can proceed with configuring a DHCP server. To configure the DHCP server for installing Virtuoizzo over the network, open the `dhcpd.conf` file (usually, it is located in the `/etc` or `/etc/dhcp` directory) for editing and add the following strings to this file:

```
next-server <PXE_server_IP_address>;
filename "/pxelinux.0";
```

**Note:** To configure a DHCP server for installation on EFI-based systems, specify `filename "/bootx64.efi"` instead of `filename "/pxelinux.0"` in the `dhcpd.conf` file (where `/bootx64.efi` is the directory to which you copied the EFI boot images when setting up the TFTP server).

## 2.5. Setting Up an HTTP Server

Now that you have set up the TFTP and DHCP servers, you need to make the Virtuoizzo distribution files available for installation over the network. To do this:

1. Set up an HTTP server. You can also use an existing HTTP server, if you have one.
2. Copy the contents of your Virtuoizzo installation DVD to some directory on the HTTP server (e.g., `/var/www/html/vz`).
3. On the PXE server, open the `/tftpboot/pxelinux.cfg/default` file for editing, and specify the path to the Virtuoizzo installation files on the HTTP server.

**Note:** For EFI-based systems, the file you need to edit has the name of `/tftpboot/pxelinux.cfg/efidefault` or `/tftpboot/pxelinux.cfg/<PXE_server_IP_address>`.

Assuming that you have the installation files in the `/var/www/html/vz` directory on the HTTP server with the IP address of 198.123.123.198 and the `DocumentRoot` directory is set to `/var/www/html`, you can add the following option to the `append` line of the `default` file to make the Virtuoizzo files accessible over HTTP:

```
method=http://198.123.123.198/vz
```

So your default file should look similar to the following:

```
default menu.c32
prompt 0
timeout 100
ontimeout VZ
menu title Virtuoizzo Boot Menu
label VZ
    menu label Install Virtuoizzo
    kernel vmlinuz
    append initrd=initrd.img ksdevice=eth0 method=http://198.123.123.198/vz
```

## 2.6. Configuring the Virtuoizzo Server

Before you can start the Virtuoizzo installation, configure each server where you plan to install the product to boot from the network. To do this:

1. Switch on the server.
2. Enter the BIOS setup.
3. Enable the network boot.



# Chapter 3. Installing Virtuozzo 7

Now that you have prepared all the servers, you can start the Virtuozzo installation:

1. Restart the Virtuozzo server after configuring its BIOS settings to boot from the network.

**Note:** If you plan to perform an unattended installation of Virtuozzo, you need to additionally create a kickstart file. See [Chapter 4, \*Creating a Kickstart File\*](#) on page 10 for information about creating kickstart files and installing Virtuozzo with these files.

2. Once the server boots, you see a dialog box asking you to select the system to install. Select the entry for Virtuozzo (**Install Virtuozzo** in our case), and press **Enter**.
3. Follow the on-screen instructions to install Virtuozzo. For details, consult the *Virtuozzo 7 Installation Guide*.

# Chapter 4. Creating a Kickstart File

If you plan to perform an unattended installation of Virtuozzo, you can use a kickstart file. A kickstart file is a simple text file containing the information used by the Virtuozzo installer to install and configure your physical server. The format of kickstart files used in Virtuozzo installations is similar to that used to perform an unattended installation of Red Hat Enterprise Linux (RHEL). To create a kickstart file, you can use your favorite text editor.

You can include in your Virtuozzo kickstart file two groups of options:

- The first group comprises the same options that you use when installing any RHEL-like distribution.
- The second group comprises the options specific to Virtuozzo.

Both groups of options are described in the following sections in detail.

## 4.1. Standard Kickstart Options

Your kickstart file may include any of the standard Linux options used in kickstart files for installing Linux operating systems. For the full list of these options and their explanations, consult the respective Linux documentation (e.g., the *Red Hat Enterprise Linux Installation Guide*).

Listed below are the mandatory options and commands that you must include in each kickstart file:

Option	Description
auth	Specifies authentication options for the Virtuozzo physical server.
bootloader	Specifies the way of installing the bootloader.
install	Tells the system to install Virtuozzo either from <code>nfs</code> or <code>url</code> (for FTP and HTTP installations, respectively). Specify this option to perform a clean installation of Virtuozzo.
keyboard	Sets the system keyboard type.
lang	Sets the language to use during installation and the default language to use on the installed system.
part	Creates partitions on the server.
rootpw	Sets the system's root password.
timezone	Sets the system time zone.
zerombr	Cleans all partition tables on disk drives.  <b>Note:</b> This option should follow <code>clearpart --all</code> .

**Notes:**

1. You can specify the `cmdline` option to install VirtuoZZo in a completely non-interactive command-line mode, without starting the X Window System.
2. When installing VirtuoZZo with VirtuoZZo storage, you can use the `autopart` option to create the default partition layout and the default configuration for chunk servers and clients. To make a custom layout and configuration, use the `part` option and create the required partitions. You will then need to use the `pstorage` command to configure the partitions for chunk serves and clients. See [Section 4.2, “VirtuoZZo Kickstart Options”](#) on page 11 for details.

## 4.2. VirtuoZZo Kickstart Options

Along with standard Linux options, VirtuoZZo provides a number of specific parameters and keywords that you need to add to your kickstart file.

The table below lists all available parameters and keywords.

**Table 4.1. General Parameters**

Parameter	Description
<code>key &lt;key&gt;</code>	Mandatory. Installs the VirtuoZZo product key on the server. This key is needed to start using the VirtuoZZo 7 software.
<code>cep [--agree --disagree]</code>	<p>Mandatory. Specify whether you want to participate in the Customer Experience Program.</p> <ul style="list-style-type: none"> <li>• <code>--agree</code>. Join the program. In this case, VirtuoZZo will periodically collect the information about the configuration of your physical server and virtual machines and containers and use it to make the product better fit your needs. No private information like your name, e-mail address, phone number, and keyboard input will be collected.</li> <li>• <code>--disagree</code>. Do not join the program.</li> </ul>
<code>vznetcfg</code>	Optional. Invokes the <code>vznetcfg</code> utility with the specified options. This parameter accepts all options that you can normally pass to <code>vznetcfg</code> . The options and their values should be separated by an equals sign (for example, <code>vznetcfg --net=virt_network1:eth0</code> ). For detailed information on the <code>vznetcfg</code> options, refer to the <b>vznetcfg</b> section in the <i>VirtuoZZo 7 Command Line Reference Guide</i> .
<code>vziptables</code>	Deprecated. To configure iptables modules for containers, use the <code>NETFILTER</code> parameter in the container configuration file (for details, see the <i>VirtuoZZo Command Line Reference Guide</i> ).
<code>vzturlmap</code>	Optional. Sets the URL of the repository and repository mirrors to use for handling EZ OS and application templates. By default, VirtuoZZo uses the following URLs:

Parameter	Description
	<ul style="list-style-type: none"> <li>• <code>http://fedora.redhat.com</code> for handling Fedora-related templates.</li> <li>• <code>http://mirror.centos.org</code> for handling CentOS-related templates.</li> <li>• <code>http://archive.ubuntu.com</code> for handling Ubuntu-related templates.</li> <li>• <code>http://download.opensuse.org</code> for handling openSUSE-related templates.</li> <li>• <code>ftp://ftp.suse.com</code> for handling SUSE-related templates.</li> <li>• <code>ftp://ftp.de.debian.org</code> for handling Debian-related templates.</li> <li>• <code>http://vzdownload.swsoft.com</code> for obtaining specific software packages for the aforementioned Linux distributions. These packages are necessary for the correct operation of your OS templates.</li> </ul> <p>To use your own URL, you first need to specify the name of the respective Linux distribution, followed by <code>=</code> and the desired URL (e.g., <code>\$FC_SERVER=http://myrepository.com</code> to redefine the default repository for Fedora). To use several URLs, separate them by space.</p> <p><b>Note:</b> Some Linux distributions (e.g., Red Hat Enterprise Linux and SUSE Linux Enterprise Server) do not have official repositories. So you should manually create software repositories before starting to use OS templates for such distributions. Refer to the <i>Virtuozzo 7 Templates Management Guide</i> to learn how you can do it.</p>
<code>up2date</code>	<p>Optional. Does the following:</p> <ol style="list-style-type: none"> <li>1. Configure the repositories with updates for Virtuozzo software and templates.</li> <li>2. Check the repositories for available updates.</li> <li>3. Download and install the updated packages, if any, on the server.</li> </ol> <p>Using this option, you can ensure that you have the latest Virtuozzo software packages and templates right after the installation, without the need to manually check for updates.</p>
<code>nosfxtemplate</code>	<p>Optional. Skips installing the pre-created and pre-cached EZ templates on the server. The current version of Virtuozzo is shipped with only one pre-created and pre-cached OS EZ template: <code>centos-6-x86_64</code>.</p>
<code>%eztemplates</code>	<p>Optional. Installs EZ templates on the server. All available templates are listed in the <code>/Packages</code> directory of the Virtuozzo distribution. You can easily identify them by the <code>-ez-&lt;number&gt;.swsoft.noarch.rpm</code> ending (e.g., <code>centos-6-x86-ez-3.0.0-14.swsoft.noarch.rpm</code>). The names of the templates</p>

Parameter	Description
	<p>must be specified without the ending and separated by the new-line character, for example:</p> <pre>%ztemplates centos-6-x86 devel-centos-6-x86</pre> <p>When using this parameter, keep in mind the following:</p> <ul style="list-style-type: none"> <li>• If you specify an empty list, no templates will be installed on the server.</li> <li>• If you skip this parameter, all templates included in the Virtuozone distribution will be installed on the server.</li> <li>• You can indicate the <code>--cache</code> argument next to a respective OS template to cache it after installation. To cache all specified OS templates, specify <code>--cache</code> after <code>%ztemplates</code>.</li> </ul> <p><b>Note:</b> To cache OS templates for some Linux distributions (e.g. Red Hat Enterprise Linux and SUSE Linux Enterprise Server), you should first create special repositories storing the necessary software packages for these OS templates. Refer to the <i>Virtuozone 7 Templates Management Guide</i> to learn how you can do it.</p> <ul style="list-style-type: none"> <li>• This option must be specified as the first one after the keys.</li> </ul>
<code>ignoredisk</code>	<p>Optional. Ignores the specified drives or all drives except the one specified. Used with one of the following arguments:</p> <ul style="list-style-type: none"> <li>• <code>--drives=&lt;drive&gt;[,...]</code> - A comma-separated list of drives to ignore. If a server has drives other than those specified in this option, the installer will ask what to do with them.</li> <li>• <code>--only-use=&lt;drive&gt;</code> - Ignore every drive except the specified.</li> </ul>
<code>prlnet [--ip-scope-start &lt;start_IP_addr&gt; --ip-scope-end &lt;end_IP_addr&gt;] [--ip &lt;adapter_IP_addr&gt;[/&lt;mask&gt;]] [--dhcp-ip &lt;DHCP_IP_addr&gt;] --name &lt;name&gt;</code>	<p>Optional. Defines the range of IP addresses the DHCP server will be able to allocate to virtual machines in host-only networks; virtual adapter IP address and subnet mask; DHCP server IP address; and virtual network name. If you omit one or more parameters, the following default values will be used:</p> <ul style="list-style-type: none"> <li>• <code>--ip-scope-start</code>: 10.37.130.1,</li> <li>• <code>--ip-scope-end</code>: 10.37.130.254,</li> <li>• <code>--ip</code>: 10.37.130.2/255.255.255.0,</li> <li>• <code>--dhcp-ip</code>: 10.37.130.1.</li> </ul>
<code>%packages</code>	<p>Specifies the package groups to install on the server:</p> <ul style="list-style-type: none"> <li>• <code>@base</code> and <code>@core</code> (mandatory). Installs the packages required for the correct operation of your system.</li> </ul>

Parameter	Description
	<ul style="list-style-type: none"> <li>• <code>@vz</code> (mandatory). Installs the packages specific to the OS virtualization part of Virtuoizzo.</li> <li>• <code>@ps</code> (mandatory). Installs the packages specific to the hardware virtualization part of Virtuoizzo.</li> <li>• <code>@clustering</code> (optional). Installs the packages required for creating clusters from Virtuoizzo systems.</li> <li>• <code>@templates</code> (optional). Installs all templates included in the Virtuoizzo distribution. If you want to install specific templates only, use the <code>%eztemplates</code> option.</li> <li>• <code>@pstorage</code> (optional). Installs the packages required for setting up a Virtuoizzo storage cluster and configuring the server as an MDS server, a chunk server, or a client.</li> <li>• <code>@optional</code> (optional). Installs additional packages that are not installed with Virtuoizzo by default.</li> </ul>

Table 4.2. Parameters Specific to Virtuoizzo storage

Parameter	Description
<pre>pstorage mds_create &lt;name&gt; --ip=&lt;IP_address&gt;</pre>	<p>Does the following:</p> <ul style="list-style-type: none"> <li>• Creates a Virtuoizzo storage cluster with the name of <code>&lt;name&gt;</code>. A name may contain the characters <code>a-z</code>, <code>A-Z</code>, <code>0-9</code> as well as minus (<code>-</code>) and underscore (<code>_</code>) signs.</li> <li>• Configures the server as a metadata server for the Virtuoizzo storage cluster and binds the MDS service to the IP address of <code>&lt;IP_address&gt;</code>.</li> </ul> <p>Metadata servers are part of any Virtuoizzo storage cluster. They store metadata about chunk servers, data chunks, and chunk replicas. You must set up at least one metadata server for a cluster to function.</p> <p><b>Notes:</b></p> <ol style="list-style-type: none"> <li>1. MDS servers must have static IP addresses assigned. If you are using DHCP, you should map an IP address to the MAC address of the MDS server.</li> <li>2. For detailed information on deploying and managing Virtuoizzo storage clusters, consult the <i>Virtuoizzo storage Administrator's Guide</i>.</li> <li>3. The current version of Virtuoizzo storage supports setting up one cluster per kickstart file. So when specifying several <code>pstorage</code> commands, make sure that all commands use the same cluster name.</li> </ol>
<pre>pstorage clusterpw &lt;passwd&gt;</pre>	<p>Mandatory. Creates a new or supplies the existing password when creating or joining Virtuoizzo storage clusters.</p>

Parameter	Description
	<p><b>Note:</b> Keeping plain-text passwords in the kickstart file is a security risk if your network is not isolated. In this case, consider installing Virtuoizzo first and configuring Virtuoizzo storage clusters manually later.</p>
<pre>pstorage mds_join &lt;name&gt; -- ip= &lt;IP_address&gt;</pre>	<p>Does the following:</p> <ul style="list-style-type: none"> <li>Configures the server as a metadata server for the Virtuoizzo storage cluster with the name of <i>&lt;name&gt;</i>.</li> <li>Sets the IP address of <i>&lt;IP_address&gt;</i> to connect to the metadata server.</li> </ul>
<pre>pstorage reg_timeout &lt;minutes&gt;</pre>	<p>Sets the number of minutes during which MDS servers, chunk servers, and clients can try to register with the master MDS server and join the cluster. Every minute, one registration attempt is made. The default value is 0, which assumes that the master MDS server is already up and running.</p>
<pre>pstorage cs_join &lt;name&gt; [&lt;options&gt;]</pre>	<p>Configures the server as a chunk server for the Virtuoizzo storage cluster with the name of <i>&lt;name&gt;</i>. You can use the following options with this command:</p> <ul style="list-style-type: none"> <li><code>--mpoint=&lt;mnt_point&gt;</code>. Specify the mount point under which the chunk server is to be mounted on the server.</li> <li><code>--ssd=&lt;MNT_POINT&gt;,&lt;SIZE&gt;</code>. Specify the mount point under which the SSD drive is to be mounted on the server.</li> <li><code>--ssd=no</code>. Specify this option to forbid the use of SSD drives for write journaling.</li> <li><code>--tier=&lt;TIER&gt;</code>. Specify the tier, from 0 to 3, defining the type of storage to use for storing data chunks. You can use tiers to keep different categories of data on different chunk servers.</li> <li><code>--allow-system-disk</code>. Allow creating chunk servers on system disks. Have in mind that doing so may result in cluster performance degradation.</li> </ul> <p>Do not use the options, except for <code>--ssd=no</code>, if you are creating the default partition layout and chunk server configuration using the <code>autopart</code> standard option.</p> <p>Chunk servers store the contents of virtual machines and containers as 64MB data chunks. All data chunks are replicated, and their replicas are stored on different chunk servers. You must set up at least one chunk server for a cluster to function.</p>
<pre>pstorage client &lt;name&gt; [-- ssd=&lt;MNT_POINT&gt; --ssd=no]</pre>	<p>Configures the server as a client for the Virtuoizzo storage cluster with the name of <i>&lt;name&gt;</i>. You can use:</p> <ul style="list-style-type: none"> <li>the <code>--ssd=&lt;MNT_POINT&gt;</code> option to manually specify the mount point under which the SSD drive is to be mounted on the server. Do not use this option if you are creating the default partition</li> </ul>

Parameter	Description
	<p>layout and chunk server configuration using the <code>autopart</code> standard option.</p> <ul style="list-style-type: none"> <li>the <code>--ssd=no</code> option to forbid the use of SSD drives for storing the local cache.</li> </ul> <p>Clients are computers with Virtuozzo 7 from where you run virtual machines and containers stored on your Virtuozzo storage.</p>
<code>pstorage key &lt;key&gt;</code>	Optional. Installs the Virtuozzo storage product key on the server. This key is needed to start using the Virtuozzo storage functionality.

## 4.3. Kickstart File Example

Below is an example of a kickstart file that you can use to install and configure Virtuozzo in unattended mode. You can use this file as the basis for creating your own kickstart files.

```
# Install Virtuozzo
install
# Uncomment the line below to install Virtuozzo in a completely unattended mode
# cmdline
# Use the path of http://example.com/vz to get the installation files.
url --url http://example.com/vz
# Use English as the language during the installation and as the default system
# language.
lang en_US.UTF-8
# Use the English keyboard type.
keyboard us
# Uncomment the line below to remove all partitions from the SDA hard drive and
# create these partitions: /boot, /, /vz, and swap.
# clearpart --drives=sda --all --initlabel
# zerombr
part /boot --fstype=ext4 --size=512
part / --fstype=ext4 --size=20096
part /vz --fstype=ext4 --size=40768 --grow
part swap --size=4000
# Use a DHCP server to obtain network configuration.
network --bootproto dhcp
# Set the root password for the server.
rootpw xxxxxxxxxx
# Use the SHA-512 encryption for user passwords and enable shadow passwords.
auth --enablesshadow --passalgo=sha512
# Set the system time zone to America/New York and the hardware clock to UTC.
timezone --utc America/New_York
# Set sda as the first drive in the BIOS boot order and write the boot record to
# mbr.
bootloader --location=mbr
# Tell the Virtuozzo installer to reboot the system after installation.
reboot
# Install the Virtuozzo license on the server.
key XXXXXX-XXXXXX-XXXXXX-XXXXXX-XXXXXX
# Create the virt_network1 Virtual Network on the server and associate it with the
# network adapter eth0.
```



```

vznetcfg --net=virt_network1:eth0
# Configure the ip_tables ipt_REJECT ipt_tos ipt_limit modules to be loaded in
# Containers.
# Use the http://myrepository.com to handle Fedora OS and application templates.
vztturlmap $FC_SERVER http://myrepository.com
# Install the listed EZ templates. Cache all OS templates after installation. Skip
# the installation of pre-created templates.
nosfxtemplate
%eztemplates --cache
centos-6-x86_64
centos-6-x86
mailman-centos-6-x86_64
mailman-centos-6-x86
# Install the packages for Virtuozzo on the server.
%packages
@base
@core
@vz
@ps

```

### 4.3.1. Kickstart file example for installing on EFI-based systems

You can use the file above to install Virtuozzo on BIOS-based systems. For installation on EFI-based systems, you need to modify the following places in the file (the changes are highlighted in bold):

```

# The following 4 commands are used to remove all partitions from the SDA hard
# drive and create these partitions: /boot/efi (required for EFI-based systems),
# /boot, /, /vz, and swap.
# clearpart --drives=sda --all --initlabel
part /boot/efi --fstype=efi --grow --maxsize=200 --size=20
part /boot --fstype=ext4 --size=512
part / --fstype=ext4 --size=20096
part /vz --fstype=ext4 --size=40768 --grow
part swap --size=4000
# Configure the bootloader.
bootloader --location=partition

```

## 4.4. Copying the Kickstart File

To install Virtuozzo using a kickstart file, you first need to make the kickstart file accessible over the network. To do this:

1. Copy the kickstart file to the same directory on the HTTP server where the Virtuozzo installation files are stored (e.g., to `/var/www/html/vz`).
2. Add the following string to the `/tftpboot/pxelinux.cfg/default` file on the PXE server:

```
ks=<HTTP_server_address>/<path_to_kickstart_file>
```

**Note:** For EFI-based systems, the file you need to edit has the name of `/tftpboot/pxelinux.cfg/efidefault` or `/tftpboot/pxelinux.cfg/<PXE_server_IP_address>`.

Assuming that the HTTP server has the IP address of 198.123.123.198, the DocumentRoot directory is set to `/var/www/html` and the full path to your kickstart file on this server is `/var/www/html/vz/ks.cfg`, your default file may look like the following:

```
default menu.c32
prompt 0
timeout 100
ontimeout VZ
menu title Virtuozzo Boot Menu
label VZ
        menu label Install Virtuozzo
        kernel vmlinuz
        append initrd=initrd.img ks=http://198.123.123.198/vz/ks.cfg
method=http://198.123.123.198/vz ksdevice=eth0
```

## 4.5. Starting Installation

Now you can start installing Virtuozzo. To do this:

1. Restart the server (see [Section 2.6, “Configuring the Virtuozzo Server”](#) on page 8).
2. After the server boots, a dialog box is displayed asking you to select the system to install. Select the entry for Virtuozzo, and press **Enter**. The installation is launched automatically and proceeds without your interaction.